



125 LOUIS STREET
SOUTH HACKENSACK, NJ 07606-1733
PHONE: 201-329-7200 FAX: 201-329-7272
E-MAIL: datamation@pobox.com
WEB: WWW.PC-SECURITY.COM

COMPU-GARD SPECIFICATIONS

COMPU-GARD MAXIMUM SECURITY ENCLOSURE MODEL CGSE-A for the Macintosh and Compaq File Servers

Enclosure

Enclosure is custom fabricated to fit each computer system, with enclosure specifically sized to the equipment secured. Enclosure size should not be significantly larger than the equipment secured so as to take up minimum desk or floor space. Specifically sized enclosures will be made available for any equipment for which security may be required during the term of the contract. Enclosure will have adequate ventilation to suit each computer to prevent overheating. Enclosure shall provide access to the power switch, floppy disk drives and cabling. Enclosure will have a rear flange that prevents the removal of boards or other internal components.

Enclosure is fabricated from 12 gauge cold rolled steel and painted with durable polyurethane paint.

Locking Bracket

The locking bracket for securing the computer inside the enclosure shall be case-hardened to prevent sawing or chiseling. The locking bracket shall be of a two-piece construction, the upper portion of which will pass through the enclosure to prevent shearing of the locks or bracket if struck by a hammer. The lower portion shall be fabricated from .25" thick steel and shall be inserted into the upper portion of the bracket to prevent shearing of locks. The upper and lower portion of the bracket shall be fastened with two 3/8-24 threaded case-hardened bolts which are not accessible when locks are inserted.

Monitor Security

The monitor is secured with vinyl coated steel aircraft cable, 60 inches in length. One end of the cable attaches within the security pad portion of the LP-1A-SEB. The other end of the cable contains a ring adapter foot which adheres to the rear of the monitor with industrial super glue.

Locks

Locks are of case-hardened barrel design, 7-pin tumbler and pick-resistant, with the capability of providing keyed alike, keyed-differently and master-keying with key series ranging from CG400 – CG2500.

Key numbers are stamped on the keys only; locks will not identify the key number.

Locks must be keyed differently according to school, class, lab or project requirements.

Installation

At the request of the Newark Public Schools, file servers with tower cases will be secured in CGSE-A enclosure and vertically mounted to side panels of desks if available, or bolted to a classroom floor.

Insurance

3 year, "No-Theft" Pledge policy with computer replacement warranty if security device is defeated and computer is stolen. Warranty is underwritten by an A-rated insurer licensed to do business in New Jersey.