



125 LOUIS STREET
SOUTH HACKENSACK, NJ 07606-1733
PHONE: 201-329-7200 FAX: 201-329-7272
E-MAIL: datamation@pobox.com
WEB: WWW.PC-SECURITY.COM

COMPU-GARD SPECIFICATIONS

SECURITY SYSTEM TO PROTECT IMAC COMPUTERS (CGLPIV-IGARD-C)

1. Housing is of two piece construction. The front is fabricated using .105" thick C.R.S. and the back using .120" thick C.R.S. and are both painted with a durable polyurethane paint.
2. Floppy or zip drive pan is fabricated using .105" thick C.R.S. and painted with a durable polyurethane paint.

Floppy or zip drive to be secured is placed inside of pan and bolted to LPIV-C. The computer will be entrapped inside of housings and bolted over pan to LPIV-C. The reverse procedure is done for removal.
3. Locking mechanism is such that when unlocked the housing fits on adapter and slides back 1" and interlocks. Locks are then inserted through top of housing and screwed into 3/8-24 panel nuts on adapter. The reverse procedure is done for removal.
4. Each security pad will have two (2) locks.
 - A. Each lock will be a barrel lock keyed alike.
 - B. Barrel lock design seven 7-pin tumbler pick resistant.
5. Each security pad will have 270 square inches of .125" thick double sided foam adhesive which can withstand 60 pounds of shear pressure per square inch of coverage. Adhesive will be recessed into bottom of security pad for added protection against attack of adhesive. Each security pad will have four (4) anti-garrots to prevent attack to adhesive with piano wire.