



125 Louis Street, South Hackensack, NJ 07606-1733  
1-201-329-7200 ● 1-212-732-3824 ● fax 1-201-329-7272  
e-mail: [datamation@pobox.com](mailto:datamation@pobox.com)  
web site: [www.pc-security.com](http://www.pc-security.com)

## **SPECIFICATIONS FOR DATAMATION UNIVERSAL SECURITY CABLE FOR DESKTOP PC's, PRINTERS & PERIPHERALS (Compu-Gard SC series kits)**

The security cable is fabricated of ¼" thick galvanized steel aircraft cable, 7" x 19" strand, vinyl coated to 5/16" diameter and is available in virtually any length. Each cable packaged is equipped with a locking washer, standard padlock, 2 keys and all fastening hardware necessary to secure any type of computer or office equipment to any type of furniture. Each security cable has a minimum breaking strength of 7,000 pounds. The features of this security cable provide the highest level of functionality because of its end-to-end design. Each security lock can be individually keyed, keyed alike in groups or Master keyed. (A reference to "Master lock" refers to providing a key that will open all locks at a particular location. "Master keyed" refers to a variety of keys controlled by a single master key. "Master Lock brand" refers to locks manufactured by Master Lock; other locks may be generic.)

### Hex Nut Fasteners DS-HNF

5/8" hex nut x ¾" long with 3/16" diameter hole for fastener in one end; 3/8" diameter access hole in opposite end; and ½" diameter hole through sides of nut for cable to pass through. This product is normally used to protect CPU internal components from being stolen.

### Hex Nut Adapter Feet DS-HNAF

Steel hex fastener is rivited to adapter foot with 3/16" diameter steel rivet. Adapter foot consists of 1/8" thick cold rolled steel washer ( 1 ¾" in diameter) molded into ¼" thick x 2" diameter 60 durometer rubber. ND Industries industrial super glue is recommended for adhering hex adapter foot to equipment.