



125 LOUIS STREET  
SOUTH HACKENSACK, NJ 07606-1733  
PHONE: 201-329-7200 FAX: 201-329-7272  
E-MAIL: [datamation@pobox.com](mailto:datamation@pobox.com)  
WEB: [WWW.PC-SECURITY.COM](http://WWW.PC-SECURITY.COM)

## COMPU-GARD SPECIFICATIONS

### **SECURITY SYSTEM TO PROTECT LARGE OFFICE EQUIPMENT (CGLPIV-C)**

SECURITY PAD 16" WIDE X 17" DEEP.

1. Housing fabricated using .105" thick C.R.S. and painted with durable polyurethane paint.
2. Adapter plate (bottom) .105" thick C.R.S. and painted with durable polyurethane paint.  
Equipment to be secured will be fastened to top of housing using adapter feet, which are adhered to bottom of equipment and bolted to plate, using 3/8-24 screws.
3. Locking mechanism is such that when unlocked the housing fits on adapter and slides back 1" and interlocks. Locks are then inserted through top of housing and screwed into 3/8-24 panel nuts on adapter plate. The reverse procedure is done for removal.
4. Each security pad will have two (2) locks.
  - A. Each lock will be a barrel lock keyed alike.
  - B. Barrel lock design seven 7 pin tumbler pick resistant.
5. Each security pad will have 270 square inches of .125" thick double sided foam adhesive which can withstand 60 pounds of shear pressure per square inch of coverage. Adhesive will be recessed into bottom of security pad for added protection against attack of adhesive. Each security pad will have four (4) anti-garrots to prevent attack to adhesive with piano wire.
6. Depending on the equipment secured, each pad may be provided with a pan, bracket or other accessory to block access to the adapter feet or other attachment.
7. Adapter Feet: Steel disc with 3/8-24 threaded hole in center molded with 60 durometer rubber to form a .250" thick x 2" diameter adapter foot which when adhered to bottom of printer, copier, fax or other office equipment will create threaded holes which can then be fastened to top plate of security pad using 3/8-24 bolts.